



TOTAL
POWER

World Leader in Synthetic Fuel Additives

The background features several dark silhouettes against a light grey background. On the left, there is a crane lifting a load. In the center, there are two oil derricks. In the foreground, there is a large silhouette of a truck. To the right, there is a silhouette of a person riding a motorcycle.

TOTAL POWER INC.

11199 Sorrento Valley Road, Suite 205

San Diego, CA. 92121

Tel +(1) 858.677.9211



www.addtpx.com

Thank you for buying TPx by Total Power!

Your fuel system will be cleaner and burn more efficiently when used consistently.

USER INSTRUCTIONS

Dosing: ½ Quart of additive will treat 125 gallons of fuel. For first time use, add enough additive to treat the entire tank. (For example: Add 2 ounces of additive to a tank that holds 15 gallons of fuel).

RECOMMENDED TO ADD BEFORE FUELING WITH NO MIXING REQUIRED

As with any fuel additives, you may want to have paper towels or rags handy to clean up any spills.

GENERAL PRECAUTIONS:

In case of contact with eyes, rinse with running water for 15 minutes. If inhaled, breathe fresh air. In case of ingestion, drink two glasses of water and do not induce vomiting (Avoid giving anything to eat or drink to an unconscious or convulsing person). In case of skin contact, remove contaminated clothing, wash skin with soap and water, and wash clothing before reuse. Seek medical attention if needed.

STORAGE:

Store in a cool, dry, well-ventilated place, DO NOT EXPOSE TO FIRE OR THE SUN. Keep containers tightly closed and out of the reach of children. Keep away from sources of ignition. TPx products are 100% biodegradable.

If for any reason you are not satisfied with your purchase, within 30 days from your order, you may return any open or unopened bottle for a full refund, minus the cost for shipping.

For return instructions and information on how to retrieve your RMA, contact us at: onlinesales@tpxtech.com